

# IP Encapsulator IPE-4000A

## MPEG-2 DVB/ATSC Encapsulator

### Features

- DVB & ATSC compliant
- Linux-based O/S
- Remote monitor/configuration using Web browser interface
- TCP to UDP tunnel support
- IRD firmware update carousel support
- Reliable operation; fully solid state (no hard drive)
- Automatic redundancy and failover support
- Support for MPE & ULE

Providing the necessary link between IP networks and broadband DVB or ATSC networks, the IP Encapsulator (IPE) 4000A enables cost effective point-to-multipoint content delivery.

The IPE-4000A is a solid state, fully embedded, Linux-based IP Encapsulator. The IPE receives IP packets from an Ethernet connection and encapsulates selected packets into an MPEG-2 transport stream per DVB or ATSC specifications. Once the IPE has encapsulated the data, it forwards the data packets based on the user configurations. The output transport stream can then be forwarded to a multiplexer or directly to a modulator for the high performance and cost saving transmission of IP data over cable, satellite or terrestrial networks.

### License Based Performance

- Field upgradeable performance via software license

### Flexible Configuration and Management

- Web-based GUI for ease of use
- SNMP remote configuration and management support
- Front panel LCD with navigation keys

### Guaranteed Interoperability

- Internet standard Quality of Service (QoS) — Type of Service (TOS) bits located in IP packet headers
- Conforms to DVB and ATSC data broadcast standards
- Compatible with IDC's Datacast XD™ Server for guaranteed file delivery and the SuperFlex® Pro Series™ Receivers.

### SMPTE 325M Support

- Provides a feedback path to support opportunistic data insertion
- Allows data to be output at varied bit rates filling available space in an existing Transport stream

### DVB-S/S2 Support

- High performance, scalable and future proof
- Enhances bandwidth efficiency

### Dependable Redundancy Support

- Support for 1:1 redundancy with minimal switching strategy
- Redundant pair share a virtual IP address
- Standby unit automatically assumes active role in the event of a failure
- Support for chain redundancy schemes
- Contact closure on fault for external switch (component redundancy)

## TECHNICAL SPECIFICATIONS—IP Encapsulator (IPE)

MODEL	DESCRIPTION
5 Mb/s	Maximum Output Rate, 1 RU DVB/ATSC Encapsulator
20 Mb/s	Maximum Output Rate, 1 RU DVB/ATSC Encapsulator
40 Mb/s	Maximum Output Rate, 1 RU DVB/ATSC Encapsulator
80 Mb/s	Maximum Output Rate, 1 RU DVB/ATSC Encapsulator
130 Mb/s	Maximum Output Rate, 1 RU DVB/ATSC Encapsulator
200 Mb/s	Maximum Output Rate, 1 RU DVB/ATSC Encapsulator



DATA THROUGHPUT CONFIGURATIONS	
IP Packet Throughput	40,000 PPS
Number of PIDs	8192
Output Data Format	MPE DSM-CC Datagram sections and data piping (EN 301 192 and ATSC 1/90 compliant)
Section Packing	Yes, selectable per PID
Firmware Carousel	Selectable bit rate; MP2TS file
Input Interface	10/100/1000 Base-TX
SNMP	MIB-II
IGMP	Version 2
PSI Tables	PAT, PMT, NIT, TDT
NETWORK SPECIFICATIONS	
Interfaces	Dual 10/100/1000 Base-TX Ethernet ports (RJ-45)
OUTPUT INTERFACE	
DVB-ASI	<ul style="list-style-type: none"> <li>Max Data Rates: 213 Mb/s</li> <li>Connectors: BNC (2)</li> </ul>
SMPTE 325M (bi-directional)	<ul style="list-style-type: none"> <li>Max Data Rates: 200 Mb/s</li> <li>Connectors: BNC (2)</li> </ul>
POWER REQUIREMENTS	
Supply Voltage	85 to 250 VAC, 50 or 60 Hz autosensing
Power Consumption	<100 Watts
PHYSICAL PARAMETERS	
Chassis	1RU rackmount
Dimensions (H, W, D)	4.5 cm x 43.2 cm x 40.6 cm (1.75" x 17" x 16")
Weight	9.53 kg (21 lbs.)
ENVIRONMENTAL CONDITIONS	
Operating Temperature	0° to 45° C (32° to 113° F)
Humidity	5% - 95% non-condensing
Shock	3.5 g @ 10 ms duration
Vibration	0.5 g @ 22-10 Hz
Air flow	Front to back
COMPLIANCE	
CB, CE, FCC, RoHS, UL/cUL	

International Datacasting Corporation is a technology provider for the world's premiere broadcasters in radio, television, data and digital cinema. IDC's products and solutions are in demand for radio and television networks, targeted ad insertion, digital cinema, 3D live events, VOD, and IPTV. IDC is headquartered in Ottawa, Canada, has installations in over 100 countries, and a strong world-wide network of value-added partners and distributors. For more information visit: [www.datacast.com](http://www.datacast.com).



HEADQUARTERS: 50 Frank Nighbor Place, Kanata, ON Canada K2V 1B9

Tel: +1 613.596.4120

Copyright © 2016 International Datacasting Corporation. Information in this document is subject to change without notice. All other trademarks are property of their owners.

[WWW.DATACAST.COM](http://WWW.DATACAST.COM)

Datasheet version #3, updated November 2016